

LOS ANGELES ABRASION TEST MACHINE



Year of Purchase: 2020

Cost: 2.55 Lac

Descriptions:

The Los Angeles Abrasion Machine is used for determination of the aggregates resistance to fragmentation. The machine consists of an electronic control unit and a rolled steel drum having an inside diameter of 711 mm and internal length of 508 mm. The drum is rotated at a speed of 31-33 r.p.m. The internal shelf provided with the machine conforms to ASTM, AASHTO and EN standards. The machine is equipped with an automatic counter, when the preset revolution count is reached, the machine will stop automatically. The drum is equipped with an interlock device which allows the operator to lock the drum into position for easy loading/unloading of the sample.

A steel tray is supplied with the machine for easy discharge of specimen and abrasive charges.

The standard model can be supplied with a safety/noise reduction cabinet. The cabinet is lined internally with soundproofing material to reduce sound level conforming to CE directives. The cabinet must be ordered with the Los Angeles machine if required, as the electronic control unit will be installed on the safety cabinet at the time of manufacture. The cabinet is equipped with an electric safety device which automatically stops the rotation of the drum when the door is opened, conforming to CE directives.

- Abrasion balls and 1.6 mm, 10mm, 11.2mm (or 12.5mm), 14 mm sieves and guard sieves (2mm, 4mm and 6mm) acc. to EN standard.

- Abrasion balls, 1.7 mm (No.12) sieve and other sieves which change depending on the grain size according to ASTM and AASHTO standards, should be ordered separately.

The Los Angeles Abrasion Machine is supplied complete with;

- Steel Tray

	UTA-0600	UTA-0601
Dimensions	850x900x950 mm	1060x1100x1210 mm
Weight (approx.)	361 kg	528 kg
Power	800 W	800 W